



LAIRD BROS (*FORFAR*) LTD

LAIRD CONCRETE SPACER BRICK

DATASHEET

INFORMATION

Lunacrete frogged concrete spacer brick are manufactured to comply with BS 6073 and are therefore subject to the special category of manufacturing control. Produced at our concrete works in Forfar using high quality aggregates internally sourced, we are able to offer split load deliveries combined with other Lunacrete products, as well as delivery by full artic load to match your requirements.

APPLICATION

Lunacrete spacer brick is designed for general coursing and for the infilling of small areas. They are an economical time saving choice as they reduce cutting and wastage. Designed to replicate our standard Lunacrete 7N block their high density and open texture, provide impressive sound insulation, while being an ideal key to render. Furthermore their low shrinkage matches the low shrinkage of our blocks making them a sensible choice in a wall with standard Lunacrete blocks.

TECHNICAL INFORMATION

CONCRETE SPACER BRICK DIMENSION	DENSITY (KG/M3)	APPROX WEIGHT (KG)	SHRINKAGE	PER PACK	MORTAR	STRENGTH (N/mm2)
215X65X100mm	2000	3.5	0.035%	512	REFER BS 5628	7.3

TO ORDER OR FOR MORE INFORMATION PLEASE CONTACT-

OLD BRECHIN RD
LUNANHEAD
FORFAR
DD8 3NQ

TEL 01307 466577
FAX 01307 468642

www.lairdbros.co.uk

All Laird Bros (Ltd) products are manufactured and sold under our Terms & Conditions of sale

