



LAIRD BROS (*FORFAR*) LTD

LAIRD CONCRETE HOLLOW BLOCK

DATASHEET

INFORMATION

Laird hollow concrete blocks are manufactured to comply with BS 6073 and are therefore subject to the special category of manufacturing control. Produced at our concrete works in Forfar using high quality aggregates internally sourced, we are able to offer split load deliveries combined with other Lunacrete products, as well as delivery by full artic load, to match your requirements.

APPLICATION

Laird hollow blocks is designed to be suitable for rough casting, while being lighter and easier to handle than solid blockwork. Where shell bedding is used added cost savings can be made, as less mortar would be required. Hollows are designed to accommodate steel reinforcement and wet concrete fill, to resist lateral/sideways loading. Furthermore their low shrinkage matches the low shrinkage of our blocks.

TECHNICAL INFORMATION

HOLLOW BLOCK DIMENSION	DENSITY (KG/M3)	APPROX WEIGHT (KG)	SHRINKAGE	PER PACK	MORTAR
440X215X215mm	2000	27	<0.05%	10	REFER BS 5628

All data herein is supplies for information only and all technical enquires, as well a pricing and ordering should be made to the following address and contact details.

OLD BRECHIN RD
LUNANHEAD
FORFAR
DD8 3NQ

TEL 01307 466577
FAX 01307 468642

www.lairdbros.co.uk

All Laird Bros (Ltd) products are manufactured and sold under our Terms & Conditions of sale